


Eigen Ceramic Range

Eigen's ceramic range is the most economical TGSI product range currently available. The durable porcelain tile is resilient and has extreme UV stability. The range has four different colours which all comply with the Luminance Contrast Standards as set out in AS/NZ 1428.4.1:2009.



Eigen Ceramic TGSI

Testing (Performed by CSIRO)

AS/NZS 4586 Appendix D
Oil Wet Ramp Test

R12

AS/NZS 1428.4
Wet & Dry Luminance Reflectance
(Ivory)

Dry 44.09/Wet 42.3

Mean Contrast Range 29.6-57.3

AS 4459.4
Breaking Load

2242N

Breaking Strength

2092N

Modulus of Rupture

31.39 N/mm²

ISO 10545-3
Water Absorption

0.19%

Colour Selection

Ivory

Charcoal

Grey

Yellow

Refer to colour system at
<http://www.eigentactile.com/>

Dimensions:

Top of Dome	25mm
Bottom of Dome	35mm
Height of Dome	5mm

Tile Dimensions:
300x300mm

Tile Thickness:
10mm

**Manufactured to AS/NZS
1428.4.1:2009**

Installation Tips:

*NB: Please see the detailed installation guide at <http://www.eigentactile.com/>

1. Lay Eigen Ceramic Tactile as you would normal tile units.
2. Tile thickness is 10mm. It is ideal to leave 13-15mm rebate in freshly laid concrete to accommodate glue and cement, and a 2-3mm gap for grouting around the tiles.